



PROFESSIONAL HEAVY DUTY CEMENT MIXER

BP500 4R



TECHNICAL SPECIFICATIONS

| Max. drum capacity (L)* | 450 | |
|---------------------------------------|----------------------------|------------------|
| Max. mixing capacity (L)* | 390 | |
| Dosage (kg) | 125 | |
| Drum rotation speed (rpm) | 25 | |
| Production per hour (m ³) | 3.3 | |
| Weight without drive unit (kg) | 240 | |
| Drive unit type | Electric / Petrol / Diesel | |
| Reinforced structure | Yes | |
| Finishing | Epoxy paint | |
| Dimensions (L x W x H) (mm)* | 1820 x 1100 x 1650 | |
| ELECTRIC MOTOR | SINGLE-PHASE | THREE-PHASE |
| Voltage (V) | 220 / 240 | 380 / 400 |
| Frequency (Hz) | 50 | 50 |
| ENGINE | HONDA | LOMBARDINI |
| Model | GX160 | 15 LD 225 |
| Fuel | Petrol | Diesel |
| Displacement (cm ³) | 163 | 224 |
| Power (kW / HP) | 3.6 / 4.8 | 3.5 / 4.8 |
| Weight (kg) | 15.1 | 28.0 |


* Tolerance $\pm 10\%$



Drum with reinforced opening and 3 double mixing blades



Lubrication point



Cast iron gear ring



Flexible axis



Poly - V cast iron and trapezoidal belt



Forklift pockets



Sole Distributor



شركة الوسام للتجارة ذ.م.م.
AL WISAM TRADING CO. L.L.C.

☎ : (+971 6) 539 03 83 ✉ : awtc@alwisamllc.com
☎ : (+971 6) 539 03 84 🌐 : www.alwisamllc.com
📍 : 81933, Sharjah - U.A.E.