

PROFESSIONAL HEAVY DUTY CEMENT MIXER

WITH HYDRAULIC LOADER

BBH400 / 500



TECHNICAL SPECIFICATIONS	BBH 400	BBH 500
Max. drum capacity (L)*	350	500
Max. mixing capacity (L)*	300	400
Water tank capacity (L)	60	60
Dosage (kg)	70	140
Drum rotation speed (rpm)	22	22
Production per hour (m³)	8	12
Approximate weight (kg)	720	750
Drive unit type	Electric / Diesel	Electric / Diesel
Reinforced structure	Yes	Yes
Finishing	Epoxy paint	Epoxy paint
Dimensions (L x W x H) (mm)*	1800 x 1800 x 2500	2000 x 2000 x 2700

ELECTRIC MOTOR	THREE-PHASE	
Voltage (V)	380 / 400	
Frequency (Hz)	50	
ENGINE	LOMBARDINI	
Model	15 LD 350	
Fuel	Diesel	
Displacement (cm³)	349	

Weight (kg) * Tolerance ±10%

Power (kW / HP)



Drum with reinforced opening and 3 double mixing blades



Reinforced drum discharge gear ring



Hydraulic control for drum tilting and in-charge hopper lifting



5.6 / 7.5

33

Lubrication point

Sole Distributor •



Water meter (optional)









3: 81933, Sharjah - U.A.E.