

## TS 300 E



### TECHNICAL SPECIFICATIONS

MODEL	TS 300 E		
Max. blade diameter (mm)	300 / 350		
Max. depth of cut (mm)	Blade Ø300 = 80 Blade Ø350 = 100		
Max. depth of with 2 runs cut (mm)	150		
Max. length of cut (mm)	695		
Arbor size (Ø mm)	25.4		
Rotation speed (rpm)	2,800		
Weight (kg)	82		
Dimensions (L x W x H) (mm)	1120 x 600 x 600		
	ELECTRIC MOTOR	SINGLE PHASE	THREE PHASE
Power (kW)		2.2	2.2
Voltage (V)		230	400
Frequency (Hz)		50	50

*TS 300 E is an efficient universal masonry saw with high cutting capacity for all kinds of bricks and building blocks. You can easily plunge or bevel cut at 45 degrees for maximum versatility. The robust single-piece frame with integrated conveyor rails gives great rigidity and provides longer product life.*

• Distributor: •



شركة الوسام للتجارة ذ.م.م.  
**AL WISAM TRADING CO. L.L.C.**

☎ : (+971 6) 539 03 83      ✉ : awtc@alwisamllc.com  
 ☎ : (+971 6) 539 03 84      🌐 : www.alwisamllc.com  
 📍 : 81933, Sharjah - U.A.E.