BATTIPAV

EXTRA SUPERLUNGA 3300S















TECHNICAL SPECIFICATIONS	
Blade (Ø mm)*	200
Max. straight cutting length (mm)	3300
Max. cutting depth for straight cut (mm)	40
Max. size tile for diagonal cutting (mm)	2330 x 2330
Max. cutting depth with 2 runs (mm)	55
Max. cutting depth for 45° angle cut (mm)	35
Tool hole (Ø mm)	25.4
Rotation speed (rpm)	2800
Motor type	1 phase - 230V ~ 50 Hz
Motor power (HP / kW)	1.8 / 1.4
Water recycling pump type	S1
Water tank capacity (Max.) (ltrs.)	25
Thermic protection (°C)	170
Amperometrical protection (A)	13
Net weight (kg)	181
Wheels kit	Included
Laser Instrument	Included
Cutting progress system	Included
Extension side bench	Included x 4 pcs.



OPTIONAL

B-Lock for thickness up to 40 mm



Side bench with rollers

A new radial tile cutter ideal for straight and 45° angle cuts on oversize porcelain tiles. A new designed bridge profile with vanguard technical innovation, strong and precise, equipped with a POWERFUL MOTOR, sliding and plunging cutting head.



3: 81933, Sharjah - U.A.E.

^{*}Diamond blade not included.