










TECHNICAL SPECIFICATIONS		OPTIONAL
MODEL	Prime 120 Prime 200	
Blade (Ø mm)*	350	 Wheels kit
Max. straight cutting length (mm)	1200 2000	
Max. cutting depth for straight cut (mm)	110	 Laser instrument
Max. size tile for diagonal cutting (mm)	845 x 845 1410 x 1410	
Max. cutting depth with 2 runs (mm)	180	 B-Lock for thickness up to 40 mm
Max. cutting depth for 45° angle cut (mm)	80	
Tool hole (Ø mm)	25.4	
Rotation speed (rpm)	2800	 Side bench with rollers
Motor type	1 phase - 230V ~ 50 Hz 3 phase - 400V ~ 50 Hz	
Motor power (HP / kW, A)	1 phase - 3.0 / 2.2, 9.0 3 phase - 4.5 / 3.4, 9.0	 Extension side bench
Water recycling pump type	S3	
Water tank capacity (Min. / Max.) (ltrs.)	26 / 41 40 / 60	 Side tile support
Thermic protection (°C)	160	
Amperometrical protection (A)	13	
Net weight (kg)	99.8 127	 Long slot for side tile support
Cutting progress system	Included	

*Diamond blade not included.

Ideal for the building sector. New design with vanguard technical innovation, strong and precise, it is suitable for cutting bricks, natural stones, concrete blocks, granite & marble slabs.

• Distributor: •



شركة الوسام للتجارة ذ.م.م.
AL WISAM TRADING CO. L.L.C.

☎ : (+971 6) 539 03 83 ✉ : awtc@alwisamllc.com
☎ : (+971 6) 539 03 84 🌐 : www.alwisamllc.com
📍 : 81933, Sharjah - U.A.E.