


















OPTIONAL



	POWER
TECHNICAL SPECIFIC	CATIONS
Blade (Ø mm)*	300
Max. straight cutting length (mm)	3200
Max. cutting depth for straight cut (mm)	85
Max. size tile for diagonal cutting (mm)	4525 x 4525
Max. cutting depth with 2 runs (mm)	135
Max. cutting depth for 45° angle cut (mm)	60
Working table dimension (L x W) (mm)	3340 x 625
Tool hole (Ø mm)	25.4
Rotation speed (rpm)	2800
Motor type	3 phase - 400V ~ 50 Hz
Motor power (HP / kW, A)	4.5 / 3.4, 6
Water recycling pump type	S3
Water tank capacity (Min. / Max.) (ltrs.)	45 / 50
Thermic protection (°C)	160
Amperometrical protection (A)	6 - 10
Net weight (kg)	205.5
Wheels kit	Included
Laser instrument	Included
Cutting progress system	Included
B-Lock for thickness up to 40 mm	Included x 2 pcs.
Side bench with rollers	Included x 1 pcs.
Extension side bench	Included x 1 pcs.
Lifting belt	Included x 1 pcs.
Additional legs for the frame	Included x (1 set = 2 pcs.)
Swivel wheels	Included x (1 set = 2 pcs.)





Side tile support



Long slot for side tile support

Ideal for straight and 45° angle cuts of ceramic, natural-stones, granite and marble slabs. A unique design due to its length cutting capacity. Able to work non-stop for 8 hours all along.



(+971 6) 539 03 83 (±) 539 03 84 ± : www.alwisamllc.com

3: 81933, Sharjah - U.A.E.

^{*}Diamond blade not included.